

Envios – LED 32W

LED TRACK HEAD PROJECTOR



DESCRIPTION

The Envios is a highly versatile adjustable track-mounted projector. Its control gear and optical compartment are kept separate; this optimizes both aesthetic balance and heat dissipation for optimal operating temperature, ensuring a high efficiency and long-lasting light source. Suitable for ceiling-mounted tracks.

LAMP/DRIVER

Lamp: LED LUCE 32W
3000K (2817 lm) & 4000K (2980 lm)
Driver: Integral electronic 120V, non-dimmable


MATERIAL

Die cast aluminum; control gear and optical compartment are separated.

SPECIFICATIONS

Luminaire: Track head + 3" IOS reflector
Adjustable: Horizontal 356°, vertical ± 90°

DIMENSIONS



PHOTOMETRIC DATA

| NS | | |
|-------|-------------|------|
| 32W | 12° (η)0.83 | |
| FC | Ø | |
| 4 ft | 1855 | 0.80 |
| 6 ft | 824 | 1.20 |
| 8 ft | 464 | 1.60 |
| 10 ft | 297 | 2.00 |
| 12 ft | 206 | 2.40 |
| 14 ft | 151 | 2.80 |

| NR | | |
|-------|-------------|------|
| 32W | 16° (η)0.81 | |
| FC | Ø | |
| 4 ft | 1048 | 1.12 |
| 6 ft | 466 | 1.68 |
| 8 ft | 262 | 2.24 |
| 10 ft | 167 | 2.80 |
| 12 ft | 117 | 3.36 |
| 14 ft | 86 | 3.92 |

| MD | | |
|-------|-------------|------|
| 32W | 22° (η)0.82 | |
| FC | Ø | |
| 4 ft | 631 | 1.52 |
| 6 ft | 281 | 2.28 |
| 8 ft | 158 | 3.04 |
| 10 ft | 101 | 3.80 |
| 12 ft | 70 | 4.56 |
| 14 ft | 52 | 5.32 |



6 Beams of Light
Narrow spot, narrow, medium, wide, wide flood & Mira 3" IOS Reflector

| WD | | |
|-------|-------------|------|
| 32W | 28° (η)0.82 | |
| FC | Ø | |
| 4 ft | 439 | 2.12 |
| 6 ft | 195 | 3.18 |
| 8 ft | 110 | 4.24 |
| 10 ft | 70 | 5.30 |
| 12 ft | 49 | 6.36 |
| 14 ft | 36 | 7.42 |

| WF | | |
|-------|-------------|-------|
| 32W | 52° (η)0.81 | |
| FC | Ø | |
| 4 ft | 174 | 3.88 |
| 6 ft | 77 | 5.82 |
| 8 ft | 43 | 7.76 |
| 10 ft | 28 | 9.70 |
| 12 ft | 19 | 11.64 |
| 14 ft | 14 | 13.58 |

| MR | | |
|-------|---------|------------|
| 32W | Mira | (η)0.69 |
| FC | 0°-180° | 90°-270° |
| 4 ft | 193 | 1.44 6.48 |
| 6 ft | 86 | 2.16 9.72 |
| 8 ft | 48 | 2.88 12.96 |
| 10 ft | 31 | 3.60 16.20 |
| 12 ft | 21 | 4.32 19.44 |
| 14 ft | 16 | 5.04 22.68 |

ORDERING GUIDE

| REG39420 | | | | 32 | | |
|----------------------------|----------------|------------|------|----------|------------------------------------------|------------------------------------------------|
| Luminaire (less reflector) | Adapter | | | Wattage | Colour Temperature | Colour |
| REG39420 | RG1 - J Track | 1 circuit | 120V | 32 - 32W | WW - 3000K, CRI 85 NN - 4000K, CRI 84 | 10 - White 21 - Black 28 - Metallic grey |
| | GL1 - H Track | 1 circuit | 120V | | | |
| | GL2 - H2 Track | 2 circuits | 120V | | | |
| | GL3 - H3 Track | 3 circuits | 120V | | | |

| Reflector (order separately) | IOS | ∠ | Lens finish |
|------------------------------|-------------|-----|-------------------|
| REG35049 | Narrow spot | 12° | Clear |
| REG35050 | Narrow | 16° | Frosted |
| REG35051 | Medium | 22° | Frosted |
| REG35052 | Wide | 30° | Frosted |
| REG35053 | Wide flood | 52° | Frosted |
| REG35054 | Mira | | Frosted prismatic |

* Please consult the liquidation page for applicable configurations