

KOLIKA - L3KOL

4' RECESSED LED



Approvals:
 CSA certified to C22.2 #250,
 ICES 005



DESCRIPTION

The Kolika LED collection offers a wide variety of styles that are ideal for illuminating and enhancing offices or commercial environments. The Kolika series allows you to achieve a consistently simple and elegant look throughout a space, without compromising the efficiency.

HOUSING AND FINISHING

The body is made of extruded aluminum, thermo-static painted with a silver-grey finish.

MOUNTING

Recessed for wall or ceiling. Delivered with support brackets. Comes with "BX" connector.

LENS


Opal

ELECTRICAL


120-277V or 347V electronic driver. Long-life LED that provide 80+ CRI are available in 3000K, 3500K, 4000K and 5000K. Estimated lifespan of over 50,000 hours to L70.

DIMENSIONS

Front view



Side view



ORDERING GUIDE

Series	Size	Lamp type	Lumen delivered (per foot)	Voltage	Colour temperature	Fixture finish	Options
L3KOL	4 - 3'10 15/16"	L - LED	S1 - 395 (92.9 lm/W) S2 - 520 (94.1 lm/W) S3 - 758 (91.3 lm/W) S4 - 975 (87.6 lm/W)	W - 120-277V H - 347V A - 120V	30K - 3000K 35K - 3500K 40K - 4000K 50K* - 5000K	S - Silver grey (standard) SP - Special colour	DIM1 - 0-10VDC dimming driver DIM2** - Line voltage dimming driver 120V DALI1* - Digital addressable lighting interface driver (Not available in 347V)

* Please consult factory for availability.
 ** Not available for the 4' S1 and S2 lumen packages.

* Please consult the liquidation page for applicable configurations